Interlocking Concrete Paving Stones



EXPAND YOUR LIVING SPACE OUTDOORS USING INTERLOCKING CONCRETE PAVING STONES FROM AIR VOL BLOCK

Create instant curb appeal by using our paving stones to craft truly distinctive driveways, walkways, plazas, and patios! Made from high-strength concrete, our concrete paving stones provide an attractive yet functional pavement which will bestow a lifetime of service. Air Vol Interlocking Concrete Paving stones are made from 8,000 psi concrete and meet or exceed the requirements of ASTM C-936 Standard Specification for Concrete Paving Stones.

ABOUT AIR VOL BLOCK

Air Vol Block, Inc. of San Luis Obispo, California is a manufacturer of quality concrete masonry units, Allan Block mortarless retaining wall systems, and interlocking concrete pavers. We also manufacture bagged dry-mix products such as Quikrete concrete mix, Mason Mix Mortar, and assorted other sacked products. To round out our product offerings, we fabricate reinforcing steel and sell a wide variety of building materials including Cultured Stone®, clay brick, and glass block.

Since its incorporation in 1962, Air Vol Block has grown with the masonry industry by focusing upon customer service, product innovation, and product quality. While we manufacture a complete line of concrete masonry units including Precision Block, Split-face Block, Slump Block, and Burnished Block, we have garnered an outstanding reputation as the go-to manufacturer for specialty shapes and sizes. We are continually upgrading our manufacturing facilities to better serve the needs of our customers The sales staff at Air Vol Block is eager and willing to assist project owners, design professionals, and contractors in the successful planning and construction of their projects! You are invited to contact us whenever we can be of service. Whether you need color samples, technical notes, or a referral to a qualified construction professional, we will do our best to help you.

DETAILED INSTALLATION AND SPECIFICATION INFORMATION IS AVAILABLE FROM OUR SALES OFFICE, OR FROM OUR WEBSITE AT AIRVOLBLOCK.COM.



Visit our outdoor showroom!



TABLE OF CONTENTS

Roman	2
Euro-Cobble	3
Tri-Cobble	2
Circle Cobble	ļ
Old World Cobble	(
Balboa	
Chumash	8
Holland	٩
Apache	10
Centurion	1
Eco-Perm & Turfpaver	12
Paver Accessories	13

Photo at left: Mixture of Sandstone and Brown/Charcoal Euro-Cobble

While all efforts were made to show product colors and textures as accurately as possible, actual product may vary from that shown in this brochure. Always request actual product color samples prior to ordering.

ROMAN

Our Roman pavers provide unlimited design possibilities as you can mix and match the three sizes and the many color options to create a truly one-of-a-kind design!

Thickness: Stocked in 60 mm. 80 mm available by special-order.



Red/Charcoal Blend Grey/Charcoal Blend Brown/Charcoal Blend Sunburst Blend

Sandstone Blend

Be sure to view actual product samples prior to ordering!



Cobble joint patterns.


Colors (Stock colors subject to change)

















Magnum

Euro-Cobble I

Euro-Cobble II



Our Tri-Cobble paver is a preblended mixture of three different sizes. Important Note: The individual pieces are not sold separately, so please be sure to install them in these approximate proportions: 5 Large Rectangles to 5 Squares to 2 small rectangles.

The rounded sides of the Tri-Cobble are conducive to creating gracefully sweeping curves.

Thickness: Stocked in 60 mm.

Packaging: 122 square feet per pallet.









Colors (Tri-Cobble and Circle Cobble) (Stock color selection subject to change)







Mixture of several color blends






Red/Charcoal Blend Charcoal
Be sure to view actual product samples prior to ordering!

Grey/Charcoal Blend Brown/Charcoal Blend Sunburst Blend

inburst Blend Sandst

Sandstone Blend




Ring #	Pieces Required	Paver Shape	Notes	Approx. Diameter (in inches)	Additional sq.ft of Tri-Cobble needed
Center	2 Center Pieces	0		4 5/8	0
Ring 1	8 Wide Wedges	\bigcirc		15	0
Ring 2	7 Wide Wedges 7 Squares		Alternate Wide Wedge and Squares	24 3/8	0
Ring 3	22 Narrow Wedges		All Narrow Wedges	33 3/4	0
Ring 4	29 Narrow Wedges		All Narrow Wedges	43 1/8	0
Ring 5	17 Narrow Wedges 17 Squares		Alternate 1 Square to 1 Narrow Wedge	52 1/2	0
Ring 6	21 Narrow Wedges 20 Squares		Alternate 1 Square to 1 Narrow Wedge	61 7/8	0
Ring 7	32 Narrow Wedges 16 Squares		Alternate 1 Square to 2 Narrow Wedges	71 1/4	0
		Create addition	Optional Rings nal rings by using Tri-Cobble Pavers		
Ring 8	Use the 3 Tri-Co	obble shapes to	create the optional rings	80 5/8	8.2
Ring 9		"		90	17.4
Ring 10		"		99 3/8	27.5
Ring 11		"		108 3/4	38.5
Ring 12		44		118 1/8	50.6
Ring 13		"		127 1/2	63.5

Center Piece

Square














/









ECO-PERM & TURFPAVER

Turfpavers and Eco-Perm Pavers provide a stable, drivable pavement while creating a permeable surface that can be designed to reduce or eliminate storm-water runoff. Either type of paver can be filled with grass or aggregate depending upon the project objectives. Planting grass in these types of pavers creates islands of cooling within the urban landscape, while allowing water to easily permeate the pavement. Filling the voids with aggregate allows the creation of underground retention basins while still maintaining use of the surface for parking.

Many possible uses:

- · Cart Paths
- Driveway Extensions
- Embankment Erosion Control
- Pathways
- Emergency Access Roads
- Environmentally Friendly Parking Areas
- Allows Air & Water to Tree Roots



ECO-PERM shown above

Thickness: 80 mm.

Coverage: 2.9 pieces per square foot based upon minimal joint pattern. Packaging: 83 square feet per pallet based upon minimal joint pattern.



See illustration to right for dimensions




Colors (Stock color selection subject to change)






Grey Brown/Charcoal Blend Be sure to view actual product samples prior to ordering!


Joint Patterns




Full Open 18.3% void Requires 2.6 pcs/sq.ft.



Running Bond 10.5% void Requires 2.9 pcs/sq.ft.



Alternating
11.7% void
Requires 2.8 pcs/sq.ft.



Minimal 7.9% void Requires 2.9 pcs/sq.ft.

TURFPAVER shown at right

Our Turfpavers are manufactured with 5,000 psi concrete and comply with ASTM C-1319 Standard Specification for Concrete Grid Pavements.


Thickness: 80 mm.

Coverage: 2.6 square feet per piece. Packaging: 130 square feet per pallet.

Colors (Stock color selection subject to change)



Be sure to view actual product samples prior to ordering!







Visit our Outdoor Showroom!

AIR VOL BLOCK ALSO STOCKS A COMPLETE LINE OF PAVER ACCESSORIES INCLUDING:

- Polymeric Joint Sand
- Edge Restraint
- Paver Sealers and Cleaners
- Construction Adhesives
- Paver Lights





#1 Suburban Rd.
San Luis Obispo, CA 93401
Tel: 805-543-1314
Fax: 805-543-0848
www.airvolblock.com